



October 18, 2011

Mr. John Everson  
Take Cover Shelters  
P.O. Box 208  
Arlington, TN 38002

Re: 12 Person Tornado Shelter

Dear Mr. Everson:

Per the recommendations of FEMA 361 "Design and Construction Guidance for Community Shelters", Second Edition 2010, the 12 person in-ground shelter has been designed using the wind load provisions of ASCE 7-05. The shelter is designed to be located in Zone VI per the manual and is designed for the design wind speed of 250 mph in exposure category C. The shelter is capable of sustaining the prescribed wind loads recommended by FEMA 361 for uplift loads, as well as the requirements for debris impact.

The purpose of this letter is to certify that the 12 person in-ground tornado shelter has been designed and built in accordance with the FEMA 361 Standards, as recommended by FEMA.

Please call if you have any questions.

Sincerely:

A handwritten signature in black ink that reads "Chad Stewart".  
A circular professional seal for Chad Evan Stewart, Registered Professional Engineer, State of Mississippi. The seal contains the text: CHAD EVAN STEWART, REGISTERED PROFESSIONAL ENGINEER, 14806, DATE, and STATE OF MISSISSIPPI.

Chad Stewart, P.E., LEED AP  
President

Chad Stewart & Associates, Inc. 8370 Highway 51 N, Suite 116, Millington, TN 38053  
Phone (901) 872-7800 Fax (901) 872-7826

Millington, TN

Knoxville, TN